

Fresh Ideas: Hatco Pizza Merchandising Solutions



How do
you want
to serve
them?





Whether you serve pizza in a restaurant, deli, supermarket, kiosk, concession stand, snack bar or deliver, Hatco has a full menu of equipment to help you succeed in today's highly competitive pizza industry.

Get a bigger slice of the pie.

People love pizza and Hatco gives you more ways to profit from its popularity. Your customers count on excellent taste, quality, value, and consistency. You can count on Hatco to safely hold your pizza piping-hot and fresh at proper serving temperatures, minimizing the risk of food-borne illness. Hatco offers a variety of warmers and merchandisers to increase your sales by reducing waste and maintaining quality. By the slice, in the box, or even the whole pie, any way you serve it, there's a Hatco pizza merchandising solution designed to help you sell more!



Glo-Ray model GRSDS-30D with optional backlit merchandising sign and accessory display sign holder (signs not included)



Glo-Ray model GRPWS-4818T for boxed or wrapped pizzas



Glo-Ray model GR2SDS-30D with Designer color inset panels

Glo-Ray heated stone shelf models GRSS-3618




Glo-Ray model GR2S-30 with Designer color inset panels and accessory pizza pans



Model GRSR-19 with Designer color and accessory pizza pan

Swanstone® Colors

Gray Granite



Bermuda Sand



Night Sky



Sawgrass





Satisfy your customers' most demanding appetite.

Increase your impulse sales—the Hatco Flav-R-Savor® and Flav-R-Fresh® Countertop Cabinets offer higher visibility of your product while balancing a precise combination of *heat* and *humidity* to extend pizza holding time. Available in a variety of *Designer* colors, these cabinets can be customized to match your décor. The tall Flav-R-Savor holds up to 16 boxed or eight bagged pizzas ready for delivery or take-out.



By the slice.



In the box.



Even the whole pie.

The Hatco Glo-Ray® line offers several opportunities for pizza holding at waitress pick-up stations, kitchen work areas, self-serve and buffet lines, pass-through holding areas, and take-out and delivery facilities. From merchandisers to heated shelves, these countertop warmers feature infrared top heat, blanket element base heat or both, to ensure food safety. Choose from six *Designer* colors to compliment your foodservice environment.



No matter how you slice it, Hatco delivers!



Glo-Ray model GR3SDS-39D with optional Designer color and accessory top sign holder (sign not included)



Glo-Ray model GRHW-1SGD with Designer color, breath protector, and accessory sign holder (sign not included)



Flav-R-Fresh model FDW-1 with rotating 4-tier circle rack and accessory pizza pans and decals



Flav-R-Savor model FSdT-2 with rotating 4-tier circle rack, optional Designer color, and accessory pizza pans and decals



Glo-Ray model GRSBF-72-S drop-in heated shelf with flush top, optional stainless steel surface, and accessory pizza pans



Thermo-Finisher™ conveyor food finisher model TFC-461R with Designer color side panels and accessory food pans



Flav-R-Savor model WFST-1X
with 4-shelf multi-purpose rack and
accessory sheet pans and decals



Glo-Ray model GRCDH-3PD
with optional Designer color
and accessory food pans



Flav-R-Savor model PFST-2X
with 8-shelf multi-purpose rack
and without humidity for boxed
or bagged pizzas




Turn your dough into more dollars.

When you order pizza, you get it the way you want it. It's the same when you order from Hatco. You have your choice from a full menu of pizza merchandising solutions designed to help you sell more, waste less, and maximize your profits. No matter how you slice it, Hatco delivers—place your order today. Contact your dealer, call 1-800-558-0607, or visit www.hatcocorp.com for more information.

Delivering more profits from your pizza!

Designer Colors

Warm Red Black Gray Granite White Granite Navy Blue Hunter Green



Nothing less than the best.™

Specifications

GRSBF-72-S 	GRSR-19 	GR2S-30 	GRSS-3618 																																								
<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>GRSBF-72-S</td> <td>120</td> <td>1750</td> <td>14.6</td> <td>62 lbs. (28 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	GRSBF-72-S	120	1750	14.6	62 lbs. (28 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>GRSR-19</td> <td>120</td> <td>420</td> <td>3.5</td> <td>21 lbs. (10 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	GRSR-19	120	420	3.5	21 lbs. (10 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>GR2S-30</td> <td>120</td> <td>450</td> <td>3.8</td> <td>39 lbs. (18 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	GR2S-30	120	450	3.8	39 lbs. (18 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>GRSS-3618</td> <td>120</td> <td>930</td> <td>7.8</td> <td>32 lbs. (15 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	GRSS-3618	120	930	7.8	32 lbs. (15 kg)
Model	Volts*	Watts	Amps	Ship. Wt.																																							
GRSBF-72-S	120	1750	14.6	62 lbs. (28 kg)																																							
Model	Volts*	Watts	Amps	Ship. Wt.																																							
GRSR-19	120	420	3.5	21 lbs. (10 kg)																																							
Model	Volts*	Watts	Amps	Ship. Wt.																																							
GR2S-30	120	450	3.8	39 lbs. (18 kg)																																							
Model	Volts*	Watts	Amps	Ship. Wt.																																							
GRSS-3618	120	930	7.8	32 lbs. (15 kg)																																							

GR2SDS-30D 	GRPWS-4818T 	GRSDS-30D with LGT-30 	GR3SDS-39D 																																													
<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>GR2SDS-30D</td> <td>120</td> <td>1640</td> <td>13.7</td> <td>174 lbs. (79 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	GR2SDS-30D	120	1640	13.7	174 lbs. (79 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>GRPWS-4818T</td> <td>120</td> <td>2055</td> <td>17.1</td> <td>175 lbs. (80 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	GRPWS-4818T	120	2055	17.1	175 lbs. (80 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>GRSDS-30D</td> <td>120*</td> <td>1530</td> <td>12.8</td> <td>140 lbs. (64 kg)</td> </tr> <tr> <td>LGT-30</td> <td>120</td> <td>41</td> <td>0.4</td> <td>30 lbs. (14 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	GRSDS-30D	120*	1530	12.8	140 lbs. (64 kg)	LGT-30	120	41	0.4	30 lbs. (14 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>GR3SDS-39D</td> <td>120/208-240</td> <td>2660</td> <td>12.4</td> <td>158 lbs. (72 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	GR3SDS-39D	120/208-240	2660	12.4	158 lbs. (72 kg)
Model	Volts*	Watts	Amps	Ship. Wt.																																												
GR2SDS-30D	120	1640	13.7	174 lbs. (79 kg)																																												
Model	Volts*	Watts	Amps	Ship. Wt.																																												
GRPWS-4818T	120	2055	17.1	175 lbs. (80 kg)																																												
Model	Volts*	Watts	Amps	Ship. Wt.																																												
GRSDS-30D	120*	1530	12.8	140 lbs. (64 kg)																																												
LGT-30	120	41	0.4	30 lbs. (14 kg)																																												
Model	Volts*	Watts	Amps	Ship. Wt.																																												
GR3SDS-39D	120/208-240	2660	12.4	158 lbs. (72 kg)																																												

GRHW-1SGD 	FDW-1 	FSDT-2 	WFST-1X 																																								
<table border="1"> <thead> <tr> <th>Model</th> <th>Volts</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>GRHW-1SGD</td> <td>120</td> <td>1650</td> <td>13.8</td> <td>71 lbs. (32 kg)</td> </tr> </tbody> </table>	Model	Volts	Watts	Amps	Ship. Wt.	GRHW-1SGD	120	1650	13.8	71 lbs. (32 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>FDW-1</td> <td>120</td> <td>1470</td> <td>12.3</td> <td>80 lbs. (36 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	FDW-1	120	1470	12.3	80 lbs. (36 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>FSDT-2</td> <td>120</td> <td>1440</td> <td>12.0</td> <td>122 lbs. (55 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	FSDT-2	120	1440	12.0	122 lbs. (55 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>WFST-1X</td> <td>120</td> <td>1790</td> <td>14.9</td> <td>163 lbs. (74 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	WFST-1X	120	1790	14.9	163 lbs. (74 kg)
Model	Volts	Watts	Amps	Ship. Wt.																																							
GRHW-1SGD	120	1650	13.8	71 lbs. (32 kg)																																							
Model	Volts*	Watts	Amps	Ship. Wt.																																							
FDW-1	120	1470	12.3	80 lbs. (36 kg)																																							
Model	Volts*	Watts	Amps	Ship. Wt.																																							
FSDT-2	120	1440	12.0	122 lbs. (55 kg)																																							
Model	Volts*	Watts	Amps	Ship. Wt.																																							
WFST-1X	120	1790	14.9	163 lbs. (74 kg)																																							

GRCDH-3PD 	PFST-2X 	TFC-461R 																															
<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>GRCDH-3PD</td> <td>120</td> <td>1960</td> <td>16.3</td> <td>222 lbs. (101 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	GRCDH-3PD	120	1960	16.3	222 lbs. (101 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>PFST-2X</td> <td>120</td> <td>1740</td> <td>14.5</td> <td>178 lbs. (81 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	PFST-2X	120	1740	14.5	178 lbs. (81 kg)	<table border="1"> <thead> <tr> <th>Model</th> <th>Volts*</th> <th>Watts</th> <th>Amps</th> <th>Ship. Wt.</th> </tr> </thead> <tbody> <tr> <td>TFC-461R</td> <td>208</td> <td>7524</td> <td>21.4</td> <td>135 lbs. (61 kg)</td> </tr> </tbody> </table>	Model	Volts*	Watts	Amps	Ship. Wt.	TFC-461R	208	7524	21.4	135 lbs. (61 kg)	
Model	Volts*	Watts	Amps	Ship. Wt.																													
GRCDH-3PD	120	1960	16.3	222 lbs. (101 kg)																													
Model	Volts*	Watts	Amps	Ship. Wt.																													
PFST-2X	120	1740	14.5	178 lbs. (81 kg)																													
Model	Volts*	Watts	Amps	Ship. Wt.																													
TFC-461R	208	7524	21.4	135 lbs. (61 kg)																													

* Other voltages available, consult factory.

See product specification sheets for additional models.

PLUG CONFIGURATIONS

Model	120 Volt 60 Hz	220 Volt 50 Hz	240 Volt 50 Hz
GRSBF-72-S	NEMA 5-20P	CEE 7/7 Schuko	—
GRSR-19	NEMA 5-15P	CEE 7/7 Schuko	BS-1363
GR2S-30	NEMA 5-15P	CEE 7/7 Schuko	BS-1363
GRSS-3618	NEMA 5-15P	CEE 7/7 Schuko	BS-1363
GR2SDS-30D	NEMA 5-15P*	CEE 7/7 Schuko	BS-1363
GRPWS-4818T	NEMA 5-20P▲	—	—
GRSDS-30D	NEMA 5-15P*	CEE 7/7 Schuko	BS-1363
LGT-30	NEMA 5-15P	—	—
GR3SDS-39D	NEMA L14-20P	—	—
GRHW-1SGD	NEMA 5-15P*	—	—

Model	120 Volt 60 Hz	208, 240 Volt 60 Hz	220 Volt 50 Hz	240 Volt 50 Hz
FDW-1	NEMA 5-15P*	—	CEE 7/7 Schuko	BS-1363
FSDT-2	NEMA 5-15P	—	CEE 7/7 Schuko	BS-1363
WFST-1X	NEMA 5-15P*	—	CEE 7/7 Schuko	BS-1363
GRCDH-3PD	NEMA 5-20P	—	CEE 7/7 Schuko	BS-1363
PFST-2X	NEMA 5-15P*	—	CEE 7/7 Schuko	—
TFC-461R	—	NEMA L15-30P	—	—

* NEMA 5-20P for Canada.
 ▲ Available in 120/208V or 120/240V, NEMA L14-20P for Canada.

Shaded areas indicate models for Export use only.



Nothing less than the best.™

P.O. Box 340500
 Milwaukee, WI 53234-0500 U.S.A.
 (800) 558-0607 (414) 671-6350
 www.hatcocorp.com
 equipsales@hatcocorp.com

Printed in U.S.A.



Form No. HPEB-2506
 March 2006