



Specifications

F.O.B Sedalia, Missouri 65301



DPAH-3M

OPTIONS:

- False Bottom - FB
- Beaded openings, 12" x 20" -HFST
- Tray shelves - PR-2, PR-3, PR-4
- Fluorescent lights - FL-2, FL-3, FL-4
- Incandescent bullet lights - BI-2, BI-3, BI-4
- Adapter bars - 513, 514, 515, 516
- Legs in lieu of casters
- Body latches
- Tray shelf on end

AGENCY LISTINGS:



DUKE MANUFACTURING CO.
2305 N. Broadway
St. Louis, MO 63102

800.735.3853 Toll Free
314.231.5074 Fax
www.dukemfg.com

Approval Stamp(s):

PRODUCT INFORMATION:

PROJECT: _____

ITEM: _____

QUANTITY: _____

MODEL:

EconoMate™ Buffet Units - Mechanically Assisted Ice Pans

- | | |
|----------------------------------|--------------------|
| <input type="checkbox"/> DPAH-2M | Portable 26" liner |
| <input type="checkbox"/> DPAH-3M | Portable 40" liner |
| <input type="checkbox"/> DPAH-4M | Portable 54" liner |

BODY:

- Heavy gauge paint grip steel
- Choice of (12) powder coat paint colors (must choose one)

<input type="checkbox"/> #217105 - Bright White	<input type="checkbox"/> #217103 - Natural Almond
<input type="checkbox"/> #217150 - Orange Red	<input type="checkbox"/> #217154 - Racing Red
<input type="checkbox"/> #217107 - Hollyberry Red	<input type="checkbox"/> #217120 - Sky Blue
<input type="checkbox"/> #217127 - Fence Green	<input type="checkbox"/> #217152 - Stone Gray
<input type="checkbox"/> #217102 - Duke Silver	<input type="checkbox"/> #217113 - Brown Kickplate
<input type="checkbox"/> #217101 - Semi Gloss Black	<input type="checkbox"/> #217125 - Textured Black
- Heavy gauge; 300 Series stainless steel top
- Clear plexiglass canopy, with black powder coat steel brackets, powder coat steel ends to match body

BASES:

- Choice of
 - Open base - O
 - Closed base - D
- 5" NSF listed black swivel casters, 2 with locks

COLD PAN COMPARTMENT:

- Fully insulated stainless steel pan
- 5" deep liner with 1" brass drain and plug
- Width of liner 19-7/8"

REFRIGERATION:

- Copper coils attached to bottom of s/s liner
- Open angle- iron base in compressor compartment
- R134A refrigerant
- On/Off switch
- Six foot cord with plug - NEMA 5-15
- Five year warranty on compressor motor

SHORT FORM SPECIFICATIONS:

Duke EconoMate Buffet Units - Mechanically Assisted Ice Pan Units.
Body shall be constructed of heavy gauge steel, painted in customer's choice of 12 powder coat paint finishes (see list above). Heavy gauge 300 Series stainless steel top shall be supplied, with easy-to-clean, clear plexiglass canopy. All bases shall be enclosed. Cold pan compartment to be fully insulated and 5" deep. Width of liner shall be 19-7/8". Unit shall be refrigerated by copper coils which are attached to bottom of stainless steel liner. Compressor compartment has open angle-iron base to support air cooled condensing unit of adequate size R134A refrigerant. On/Off switch and cord with plug to be provided. Entire unit shall be factory tested, with five year warranty on compressor motor only. Units shall be mounted on 5" NSF listed swivel casters, two with locks. Canopy adds 12-3/4" to width and 20" to height of units. **NOT AVAILABLE IN TABLE TOP MODELS.**


ECONOMATE BUFFET UNITS - COLD UNITS - MECHANICALLY ASSISTED ICE

Catalog No. EMB-MECHCOLD


A.I.A. File No. 35-C-13

EMB-04

EconoMate®



TOP VIEW




FRONT VIEW

EconoMate Buffet Units Mechanically Assisted Ice Pans

- DPAH-2M Portable 26" liner
- DPAH-3M Portable 40" liner
- DPAH-4M Portable 54" liner

NOT AVAILABLE IN TABLE TOP MODELS

LEGEND	
▲	- ELECTRICAL CONNECTION
●	- DRAIN LOCATION
R134A refrigerant	



SIDE VIEW

DIMENSIONS:

FREIGHT CLASS: 100

Model	Length		Width		Height		Liner Dimensions in.			Cube ft. Crated	Weight	
	in.	cm	in.	cm.	in.	cm	L	W	D		lbs.	kg
DPAH-2M	30-3/8	77.2	22-1/2	57.2	33-3/8	84.8	26	19-7/8	5	23.1	244	110.9
DPAH-3M	44-3/8	112.8	22-1/2	57.2	33-3/8	84.8	40	19-7/8	5	32.0	291	132.3
DPAH-4M	58-3/8	148.3	22-1/2	57.2	33-3/8	84.8	54	19-7/8	5	40.9	322	146.4

ELECTRICAL SPECIFICATIONS:

Model	120 Volt		
	HP	Amps	NEMA
DPAH-2M	1/5	4.2	5-15
DPAH-3M	1/5	4.2	5-15
DPAH-4M	1/4	5.2	5-15

DUKE MANUFACTURING CO.

2305 N. Broadway
St. Louis, MO 63102

800.735.3853 Toll Free
800.231.1130 In Missouri
314.231.5074 Fax
www.dukemfg.com



Specification subject to change